

F61 Stop Ends

Scope of Use / Specification Sheet

SharkBite® plumbing fittings and pipe are manufactured in Australia at RWC's state of the art facilities. Stringent quality control and advanced manufacturing procedures guarantee product satisfaction.

SharkBite® is an advanced design push-to-connect plumbing system for potable water distribution. SharkBite® is available in an assortment of over 200 fittings and PEX pipe ranging from 16-25mm size. SharkBite® has been engineered with ease of use and disconnection in mind and while being the most dependable way to join copper and PEX Pipe in any combination with no soldering, clamps, unions or glue.

Product Code		
Code	Size / Model	
F514	16mm	
F518	20mm	
F520	25mm (DN25Cu)	




F514

Features and Benefits

- Quick and easy to install in both wet or dry conditions
- No expensive tools required supplied ready for installation
- Approved for behind the wall application
- Approved for underground installation with SharkBite Silicone Wrap (F708)
- Instant push-to-connect connection. Cut. Push. Done.
- Removable after installation
- Intergral tube liner for PEX installations means no loose components and ensures a secure reliable connection

Materials	
Body	DZR Brass
Grab Ring	316 Stainless Steel
O-Ring	EPDM
Tube Liner	Polysulfone (PEX fittings only)






All SharkBite fittings are guaranteed against defects in materials or manufacturing for a period of 25 years from the date of purchase.



F61 Stop Ends



Model Dimensions				
Code	1	L		
F514	16 OD	26		
F518	20 OD	31		
F520	25 OD (DN25Cu)	35		

Note: All measurements in mm unless otherwise stated.

Working Pressures and Temperatures				
Pipe	Pressure/Temperature			
PEX SDR9	Designed for operating at 2000kPa / 20°C	Max operating values of 1000kPa / 70°C		

PEX Dimensions						
Nominal Outside Diameter	16mm	20mm	25mm			
Average Wall Thickness	2.15mm	2.45mm	3.00mm			
Average Internal Diameter	11.7mm	15.2mm	19.1mm			

Installation

Installation is subject to the requirements of the applicable regulatory authority, the National Construction Code Volume Three – Plumbing Code of Australia, associated reference standards as applicable at the time and AS/NZS 3500.1.

Standards and Approvals



Warranty

Reliance Worldwide Corporation (Aust.) Pty. Ltd. (RWC) will either replace or repair any defective goods where the defect arose as a result of manufacture within the warranty period. You may contact RWC at the phone number, address or e-mail shown below for further information or to make a claim.

Visit www.rmc.com.au/warranty to view the warranty statement in full and for further important information.

