

Silicone Burial Wrap

Scope of Use / Specification Sheet

RWC Silicone Burial Wrap is a ready-to-use weatherproof tape that creates a watertight and airtight seal by bonding to itself within minutes. Resistant to UV, oil, salt and corrosive chemicals, RWC Silicone Wrap has a stretch capacity of 300% and is suitable for working temperatures of -54°C to +260°C. RWC Silicone Burial Wrap conforms easily to any surface making it ideal for sealing plumbing repairs and installations.



VC870

Product Code

Code	Size
VC870	50mm x 3m (Self-adhesive)

Installation

When using RWC Silicone Burial Wrap, make a connection as per AS/NZS 3500. While leaving the protective film in place, measure the amount of tape needed to completely wrap the fitting.

To ensure a proper seal, overlap tape by 25mm past the end of the fitting on every end and 5mm – 10mm between/across the fitting.

Completely cover the fitting by wrapping (overlapping each edge of the tape) the fitting, pulling the tape tight and removing the protective film. The tape will bond to itself within minutes and form an impervious barrier within a few hours.

Features and Benefits

- Strong wrap used on plumbing fittings when buried
- Corrosion resistant
- Stretches up to 300%
- Bonds within minutes
- Forms an impervious barrier within a few hours

Specification Data

Materials	Thickness	Working Temperature
Silicone Rubber	0.5mm	-54°C to +260°C