AUSTRALIAN MADE AND OWNED



SharkBite® fittings and pipe are manufactured in Australia by Reliance Worldwide Corporation (Aust.)
Pty. Ltd. in state of the art facilities.
Stringent quality control and advanced manufacturing procedures guarantee product satisfaction.

25 YEAR WARRANTY⁽²⁾



The SharkBite® range of fittings and PEX pipe can be relied upon to perform year after year. SharkBite® is backed by the Reliance Worldwide Corporation (Aust.) Pty. Ltd. 25 year warranty.

VERSATILE AND REUSABLE



Can be easily disconnected using the SharkBite® Disassembly Clip or Tongs. Fittings can be rotated once installed, allowing for a more versatile, easier use, especially in confined spaces. This feature is particularly useful where repairs and or maintenance are required.

OUICK AND EASY



SharkBite® is quick and easy to install, making it the most time effective plumbing system available, allowing the installer to move onto the next job faster than ever before.

Utilising state of the art push-to-connect design, DR brass fittings, the SharkBite $^{\oplus}$ system is easily assembled by hand.

SHARKBITE® SYSTEM CONVERSION



SharkBite® offers a range of conversion fittings that adapt to existing SDR 7.4, SDR 9, Polybutylene and Copper piping systems.

STANDARDS APPROVED



SharkBite® fittings and PEX pipe comply with and are approved to Australian Standards AS 2537 and AS 2492 – 1994 respectively.

SHARKBITE®

PLUMBING SYSTEM

SharkBite® has established a reputation as the world's #1 push-to-connect plumbing system.

- Quick and easy to use
- Fittings for PEX and Copper Pipe
- Conversion Fittings to other pipe systems
- Assemble by hand, no costly tools
- For use on hot and cold water
- Approved for behind walls and in ground (1)
- Can be disconnected and reconnected
- Australian made and owned
- 25 year warranty⁽²⁾
- For a copy of the Technical Manual, refer to the SharkBite® website

(1) Buried in ground fittings must be wrapped using Silicone Wrap.
(2) See our website for further information on SharkBite® warranty.

Contents of this brochure are subject to change, please visit our website for most up-to-date product information.

SharkBite









O sharkbite.au

27-28 Chapman Place Eagle Farm QLD 4009, Australia



Reliance Worldwide Corporation (Aust) Pty. Ltd. ABN 71 004 784 301 | AU-SB-MN0205R1



NOTHING BEATS THE SHARK



CONVERSION FITTINGS



VERSATILITY, EFFICIENCY & RELIABILITY

Whether Copper, PEX or Polybutylene, SharkBite® has you covered with a comprehensive range of piping system adaptors that will ensure easy connection to most systems.

Available through all reputable plumbing supply outlets in Australia, SharkBite® provides versatility, efficiency and reliability.



PEX FITTINGS





- Fittings can be installed on wet pipe even with water flowing
- Fittings can be disconnected and reconnected as required


INSTALLATION OF PEX PIPE

Safe Seal Indicator Marks



Cut

Using SharkBite® PEX Pipe Cutters, cut the pipe squarely between two of the SharkBite® safe seal indicator marks as shown in the picture. Ensure pipe is round, clean and free of debris.




Push

Insert the pipe through the release collar to rest against the grab ring. Push the pipe firmly with a twisting action and push to the SharkBite® safe seal indicator mark.



Done

Ensure the SharkBite® safe seal indicator mark aligns with the release collar as shown.



Disassembly

Using the Disassembly Tongs or Clip, fittings can be easily changed, removed and the fittings reused.

INSTALLATION FOR PEX AND COPPER PIPE ARE AS PER AS 3500

COPPER FITTINGS



- Used to connect copper systems
- Copper fittings have black coloured ends
- A range of fittings and adapters are available
- Fittings are rotatable after connection
- Fittings can be installed on wet pipe even with water flowing
- Fittings can be disconnected and reconnected as required

INSTALLATION OF COPPER PIPE



Cut

Using a pipe cutter, cut the copper tube to length making sure the pipe is cut squarely. Ensure pipe is round, clean and free of debris.



Deburr

Remove burrs from the pipe using the SharkBite® deburrer and depth gauge.



Mark

Mark the pipe with a marker using the depth gauge.



Push

Insert the pipe by pushing firmly until a positive click is heard.



Done

Ensure the mark made with depth gauge aligns with the release collar.



Disassembly

Using the Disassembly Tongs or Clip, fittings can be easily changed, removed and the fittings reused.





















F1 Straight Couplings

F008	16mm OD x 16mm OD
F016	20mm OD x 20mm OD
F020	25mm OD (DN25Cu) x 25mm OD (DN25Cu)



F058	20mm OD x 16mm OE
F060	25mm OD (DN25Cu)
	x 20mm OD



16mm OD x 15F

F088 20mm OD x 20Fl

Connectors

F3 Straight Male Connectors F120 16mm OD x 15MI

F116	16mm OD x 20MI
F138	20mm OD x 15MI
F134	20mm OD x 20MI
F142	25mm OD (DN25Cu) x 20I
F1/(O	25mm OD (DN25Cu) v 25M



25mm OD (DN25Cu)

F13 Male Elbows

F248 16mm OD x 16mm OD F280 16mm OD x 15MI 20mm OD x 20mm OD 25mm OD (DN25Cu) x F286 16mm OD x R³/₄"-20



F14 Female Elbows F308 16mm OD x 15FI 20mm OD x G3/4'

F15BP Backplate Female Elbows F334 16mm OD x 15FI

F340

20mm OD x 20Fl



F352 16mm OD x 15Ml x 100mm F354 20mm OD x 20Ml x 185mm F356 20mm OD x 15Ml x 100mm







15FI Nut

20FI Nut

20mm OD x

F63 Bent Tap Connectors F532 16mm OD

x 15FI 20mm OD x F536 20FI



PEX Tail /

Capillary Tail

F608 16mm OD Tail

x 15 Cap Tail 20mm OD Tail

16mm OD x 15MI x 185mm

Top-Plated Male Elbows

16mm OD x 15MI x 100mm F336-230 15MI x 230mm

Recycled BP's F339-90

20mm SB x 5/8" BSP x 90mm 20mm SB x 5/8" F339-200 BSP x 200mm

F24 Equal Tees

F362 16mm OD x 16mm OD x 16mm OD F370 20mm OD x 20mm OD x 20mm OD F374 25mm OD (DN25Cu) x 25mm OD F374 (DN25Cu) x 25mm OD (DN25Cu)



F61 Stop Ends F514 16mm OD

20mm OD x 20mm OD x 16mm OD 25mm OD (DN25Cu) x 25mm OD (DN25Cu) x 20mm OD F520 20mm OD x 16mm OD x 20mm OD 20mm OD x 16mm OD x 16mm OD

Recessed - Straight



Right Angled Breech

200mm 150mm









F609

Copper Adaptors

F600 16mm OD Tail x 15 Cu F602 16mm OD Tail x 20 Cu 20mm OD Tail x 15 Cu F606 20mm OD Tail x 20 Cu

Flare Adaptors

F610 16mm OD x 15 Flare F612 20mm OD x 20 Flare

Ball Valves 16mm OD x 16mm OD 20mm OD x 20mm OD 25mm OD (DN25Cu) x BVF670 BVF674 25mm OD (DN25Cu) BVF680 16mm OD x 15FI 20mm OD x 20Fl

25mm OD x 25Fl

Right Angled Breech

300mm F642 200mm (While stocks last)

All breech outlets must be supported to restrict movement.

Breech



PEX Tail Reducers

F720 16mm OD Tail x 20 OD

16mm OD Tail x 25 OD

20mm OD Tail x 25 OD

Manifolds F690-3T

20mm OD x 3 Way 16mm PEX Take Offs x 20mm OD 20mm OD x 4 Way 16mm F690-4T PEX Take Offs x 20mm OD

COPPER FITTINGS

SHARKBITE® 25MM OD PEX CONNECTIONS CAN BE USED FOR PEX OR COPPER (DN25CU)

BVF684





RA058 DN20 x DN15 DN25 (25mm OD) x DN20



No2 Female Connectors

RA072 DN15 x 15mm FI RA088 DN20 x 20mm F



No3 Male Connectors RA120 DN15 x 15mm MI



Hot Water Elbows RA380 DN15 x 20mm MI



No12 Elbows RA248 DN15



Elbows RA334 DN15 x 15mm F



RA350 DN15 x 15mm MI 75mm

DN15 x 15mm MI 185mm

No1 Straight Couplings RA008 DN15



RA412 DN20 x DN20 x DN15



No61 Stop Ends



Slip Couplings



DN20 x DN20 Flare



SharkBite Tail x RA720 DN15 x DN20 Tail



No24 Equal Tees



DN20 x DN15 x DN15 DN25 (25mm OD) x DN25 (25mm OD) x DN20







16mm OD x

20mm OD x

20mm SDR9

BVRA670 DN15 x DN15 BVRA672 DN20 x DN20 DN15 x 15mm F BVRA680 BVRA682

CONVERSION FITTINGS - COPPER





Couplings

Elbows 16mm OD to 16mm OD to F250 DN15 Cu 20mm OD to DN15 Cu 20mm OD to DN20 Cu DN20 Cu

SDR9 PEX to Copper

SDR9 PEX to Copper **Ball Valves** BVFRA009 16mm OD x DN15 Cu BVFRA017 20mm OD x

F363 DN20 Cu

SDR9 PEX to Copper Copper Centre Tees* 16mm OD to 20mm OD to F372 DN20 Cu

SDR9 PEX to Copper SharkBite Centre Tees* F364 16mm OD to DN15 Cu 20mm OD to DN20 Cu

*Copper must comply to AS 1432

CONVERSION FITTINGS - PEX





16mm OD

20mm OD

20mm OD x

SDR9 to Polybutylene

SDR9 to SDR9 PEX Couplings Couplings F009PB 16mm OD x FO09AP 18mm PB 20mm OD x

22mm PB



20mm OD x



16mm OD x

20mm OD x

20mm OD 22mm PB **Note:** PEX Conversion Fittings are **NOT** suitable for connection on aluminium multi-layer PEX Systems

PIPE



Potable Water (Mustard) XF860 XF864 16mm OD 5m Straight 16mm OD 50m Coil XF864100 16mm OD 100m Coil 20mm OD 5m Straight 20mm OD 50m Coil

XF874100 20mm OD 100m Coil XF880 25mm OD 5m Straight



XF860R 16mm OD 5m Straight
 KF864R
 Infilition of sin straight

 KF870R
 20mm OD 5m Straight

 XF874R
 20mm OD 5m Coil

 XF880R
 25mm OD 5m Straight

 XF882R
 25mm OD 25m Coil



Recycled Water (Purple) XF862L 16mm OD 25m Coil . 20mm OD 5m Straight 20mm OD 25m Coil



Tempering Valves

with SharkBite® Copper Fittings

MIXRA11009I 15mm Cu Insulated Standard
MIXRA11116I 15mm Cu Insulated Ultra Solar

Rain Water (Green) XF860G 16mm OD 5m Straight XF862G 16mm OD 25m Coil XF870G 20mm OD 5m Straight XF872G 20mm OD 25m Coil XF880G 25mm OD 5m Straight XF882G 25mm OD 25m Coil



Pipe in Conduit (Mustard only)

29mm ID Black to suit 25mm

XF863 16mm OD 25m Coil XF873 20mm OD 25m Coil

Corrugated Sleeve - Conduit Only 23mm ID Black to suit 16mm OD & 20mm OD 25m Coil



XF882RR3 25m x 25mm pre-insulated PEX R0.3 XF862RR8 25m x 16mm pre-insulated PEX R0.8 XF872RR8 25m x 20mm pre-insulated PEX R0.8 XF882RR8 25m x 25mm pre-insulated PEX R0.8

PIPE PROTECTION & SUPPORT _



Tube Clips

F820 16mm OD Timber Nail F830 20mm OD Timber Nail F850 25mm OD Timber Nail 16mm OD Masonry Nail 20mm OD Masonry Nail F832 25mm OD Masonry Nail 16mm OD Tek Screw F824 F834 20mm OD Tek Screw F854 25mm OD Tek Screw F826 16mm OD Concrete Anchor 20mm OD Concrete Anchor F836 16mm OD Metal Stud 20mm OD Metal Stud




F838

F704 200m Flat Coil Note: To suit 16mm, 20mm & 25mm SB



F04U	10111111	
F842	20mm	
F844	25mm	

Tube Bend Supports



RWC Silicone Burial Wrap

TEMPERING VALVES

with SharkBite® PEX Fittings

TOOLS & ACCESSORIES



16mm PEX Standard 16mm PEX Insulated Ultra Solar





4 in 1 Tempering Valves - DOWN

MIX11014D Mix 16mm SB MIX11013D Mix 20mm SB



4 in 1 Tempering Valves - UP MIX11014U Mix 16mm SB MIX11013U Mix 20mm SB



Pipe De-Coilers UFH034 Pipe De-Coiler

Note: For use with 16mm & 20mm, 50m & 100m coils









Disassembly Clips





F702 DN15, DN20, DN25











