

PEX FITTINGS

SHARKBITE® 25MM OD PEX CONNECTIONS CAN BE USED FOR PEX OR COPPER (DN25CU)



F1 Straight Couplings
F008X 16mm OD x 16mm OD
F016X 20mm OD x 20mm OD
F020X 25mm OD (DN25Cu)
x 25mm OD (DN25Cu)



F1R Reducing Couplings
F058X 20mm OD x 16mm OD
F060X 25mm OD (DN25Cu)
x 20mm OD



F2 Straight Female Connectors
F072X 16mm OD x 15FI
F068X 16mm OD x 20FI
F088X 20mm OD x 20FI
F094X 25mm OD* x 25FI



F3 Straight Male Connectors
F120X 16mm OD x 15MI
F116X 16mm OD x 20MI
F138X 20mm OD x 15MI
F134X 20mm OD x 20MI
F142X 25mm OD (DN25Cu) x 20MI
F140X 25mm OD (DN25Cu) x 25MI



F12 Elbows
F248X 16mm OD x 16mm OD
F256X 20mm OD x 20mm OD
F260X 25mm OD (DN25Cu) x
25mm OD (DN25Cu)




F13 Male Elbows
F280X 16mm OD x 15MI
F286X 16mm OD x R¾"-20




F14 Female Elbows
F308X 16mm OD x 15FI
F314X 20mm OD x G¾"



F15BP Backplate Female Elbows
F334X 16mm OD x 15FI
F340X 20mm OD x 20FI



F19BP Backplate Male Elbows
F350X 16mm OD x 15MI x 75mm
F351X 16mm OD x 15MI x 185mm
F352X 16mm OD x 15MI x 100mm
F354X 20mm OD x 20MI x 185mm
F356X 20mm OD x 15MI x 100mm
F358X 20mm OD x 15MI x 200mm



Top-Plated Male Elbows
F336X 16mm OD x 15MI
x 100mm
F336X-230 16mm OD x 15MI
x 230mm



F24 Equal Tees
F362X 16mm OD x 16mm OD x 16mm OD
F370X 20mm OD x 20mm OD x 20mm OD
F374X 25mm OD (DN25Cu) x 25mm OD
(DN25Cu) x 25mm OD (DN25Cu)



F25, F26, F27 Unequal Tees
F412X 20mm OD x 20mm OD x 16mm OD
F416X 25mm OD (DN25Cu) x 25mm OD
(DN25Cu) x 20mm OD
F444X 20mm OD x 16mm OD x 20mm OD
F454X 20mm OD x 16mm OD x 16mm OD



F61 Stop Ends
F514X 16mm OD
F518X 20mm OD
F520X 25mm OD
(DN25Cu)



F62 Straight Tap Connectors
F526X 16mm OD x
15FI Nut
F530X 20mm OD x
20FI Nut



F63 Bent Tap Connectors
F532X 16mm OD
x 15FI



PEX Tail / Copper Adaptors
F600X 16mm OD Tail x 15 Cu
F606X 20mm OD Tail x 20 Cu



PEX Flare Adaptors
F610X 16mm OD x 15 Flare
F612X 20mm OD x 20 Flare



Ball Valves
F670X 16mm OD x 16mm OD
F672X 20mm OD x 20mm OD
F674X 25mm OD (DN25Cu) x 25mm
OD (DN25Cu)
F680X 16mm OD x 15FI
F682X 20mm OD x 20FI
F684X 25mm OD x 25FI (DN25Cu)



Recessed Right Angled Breech
F630X 300mm
F632X 200mm



Shower Right Angled Breech
F650X 200mm
F652X 150mm



Manifolds
F690X-3T 20mm OD x 3 Way 16mm PEX
Take Offs x 20mm OD

All breech outlets must be supported to restrict movement.

COPPER FITTINGS

SHARKBITE® 25MM OD PEX CONNECTIONS CAN BE USED FOR PEX OR COPPER (DN25CU)



No1 Straight Couplings
RA008X DN15
RA016X DN20



No1R Reducing Couplings
RA058X DN20 x DN15



No2 Female Connectors
RA072X DN15 x 15mm FI
RA088X DN20 x 20mm FI



No3 Male Connectors
RA120X DN15 x 15mm MI
RA134X DN20 x 20mm MI



Hot Water Elbows
RA380X DN15 x 20mm MI



No12 Elbows
RA248X DN15
RA256X DN20



No15BP Female Lugged Elbows
RA334X DN15 x 15mm FI
RA340X DN20 x 20mm FI



No19BP Male Lugged Elbows
RA350X DN15 x 15mm MI 75mm
RA352X DN15 x 15mm MI 100mm



No24 Equal Tees
RA362X DN15
RA370X DN20




No25 Unequal Tees
RA412X DN20 x DN20 x DN15



No61 Stop Ends
RA514X DN15
RA518X DN20



Slip Couplings
RA3008X DN15
RA3016X DN20



Ball Valves
RA670X DN15 x DN15
RA672X DN20 x DN20
RA682X DN20 x 20mm FI
RA683X DN20 x 20mm MI

CONVERSION FITTINGS - COPPER



SDR9 PEX to Copper Couplings
F009X 16mm OD to
DN15 Cu
F017X 20mm OD to
DN20 Cu



SDR9 PEX to Copper Elbows
F250X 16mm OD to
DN15 Cu
F258X 20mm OD to
DN20 Cu



SDR9 PEX to Copper SharkBite Centre Tees*
F363X 16mm OD to
DN15 Cu
F371X 20mm OD to
DN20 Cu
F364X 16mm OD to
DN15 Cu
F372X 20mm OD to
DN20 Cu

*Copper must comply to AS 1432

CONVERSION FITTINGS - PEX



SDR9 to SDR7.4 PEX Couplings
F009XPX 16mm OD x
16mm OD
F017XPX 20mm OD x
20mm OD



SDR9 to Polybutylene Couplings
F009XPB 16mm OD x
18mm PB
F017XPB 20mm OD x
22mm PB



SDR9 to SDR9 PEX Couplings
F009XAP 16mm OD x
16mm SDR9
F017XAP 20mm OD x
20mm SDR9



SDR9 to SDR7.4 PEX SharkBite Centre Tees
F364XPX 16mm OD x
16mm OD
F372XPX 20mm OD x
20mm OD



SDR9 to Polybutylene SharkBite Centre Tees
F364XPB 16mm OD x
18mm PB
F372XPB 20mm OD x
22mm PB

Note: PEX Conversion Fittings are NOT suitable for connection on aluminium multi-layer PEX Systems


PIPE



Potable Water (Mustard)
XF860 16mm OD 5m Straight
XF864 16mm OD 50m Coil
XF864100 16mm OD 100m Coil
XF870 20mm OD 5m Straight
XF874 20mm OD 50m Coil
XF874100 20mm OD 100m Coil
XF880 25mm OD 5m Straight
XF882 25mm OD 25m Coil



Hot Water (Red)
XF860R 16mm OD 5m Straight
XF864R 16mm OD 50m Coil
XF870R 20mm OD 5m Straight
XF874R 20mm OD 50m Coil
XF880R 25mm OD 5m Straight
XF882R 25mm OD 25m Coil



Recycled Water (Purple)
XF862L 16mm OD 25m Coil
XF870L 20mm OD 5m Straight
XF872L 20mm OD 25m Coil
XF882L 25mm OD 25m Coil



Rain Water (Green)
XF860G 16mm OD 5m Straight
XF862G 16mm OD 25m Coil
XF870G 20mm OD 5m Straight
XF872G 20mm OD 25m Coil
XF880G 25mm OD 5m Straight
XF882G 25mm OD 25m Coil



Pipe in Conduit (Mustard only)
XF863 16mm OD 25m Coil
XF873 20mm OD 25m Coil



Corrugated Sleeve - Conduit Only
F706 23mm ID Black to suit 16mm OD &
20mm OD 25m Coil
F707 29mm ID Black to suit 25mm OD
25m Coil



Foam Pipe Insulation (Red only)
XF862RR3 25m x 16mm pre-insulated PEX R0.3
XF872RR3 25m x 20mm pre-insulated PEX R0.3
XF882RR3 25m x 25mm pre-insulated PEX R0.3
XF862RR8 25m x 16mm pre-insulated PEX R0.8
XF872RR8 25m x 20mm pre-insulated PEX R0.8
XF882RR8 25m x 25mm pre-insulated PEX R0.8

PIPE PROTECTION & SUPPORT



Tube Clips
F820 16mm OD Timber Nail
F830 20mm OD Timber Nail
F850 25mm OD Timber Nail
F822 16mm OD Masonry Nail
F832 20mm OD Masonry Nail
F852 25mm OD Masonry Nail
F824 16mm OD Tek Screw
F834 20mm OD Tek Screw
F854 25mm OD Tek Screw
F826 16mm OD Concrete Anchor
F836 20mm OD Concrete Anchor
F828 16mm OD Metal Stud
F838 20mm OD Metal Stud



Chasing Sleeves
F704 200m Flat Coil
Note: To suit 16mm, 20mm & 25mm SB



RWC Silicone Burial Wrap
VC870 50mm x 3m (Self-adhesive)



Tube Bend Supports
F840 16mm
F842 20mm
F844 25mm

TEMPERING VALVES

TEMPERING VALVES NOT MADE FROM LEAD FREE BRASS



Tempering Valves with SharkBite® PEX Fittings
MIXSB16 16mm PEX Standard
MIXFI1116I 16mm PEX Insulated Ultra Solar



Tempering Valves with SharkBite® Copper Fittings
MIXRA11009I 15mm Cu Insulated Standard
MIXRA11116I 15mm Cu Insulated Ultra Solar



4 in 1 Tempering Valves - DOWN
MIXI1014D Mix 16mm SB
MIXI1013D Mix 20mm SB



4 in 1 Tempering Valves - UP
MIXI1014U Mix 16mm SB
MIXI1013U Mix 20mm SB

TOOLS & ACCESSORIES



Pipe De-Coilers
UFH034 Pipe De-Coiler
Note: For use with 16mm & 20mm,
50m & 100m coils



Tube Cutters
F700 16mm OD to 25mm OD (Ratchet)
F701 16mm OD to 25mm OD



Disassembly Clips
F710 16mm OD
F712 20mm OD and DN20Cu
RA710 DN15Cu



Copper Deburrers & Depth Gauges
F702 DN15, DN20, DN25